

Series TEL

48m TEL - Normal

Description:

The given tower is designed as an equilateral triangle, with a fully welded steel lattice structure, composed by legs and bracings made of solid round bars.

The tower is prepared for installation of a 2 m toppole.

Specification:

Total theoretical tower weight = 8170 kg

Leg distance at tower base = 1800 mm

Foundation bolts: 12 x M36

The steel is hot dip galvanized according to DIN/EN ISO 1461.

The design of the lattice tower is made according to:

DIN/EN 1993-3-1 – Design of steel structures – Towers, masts and chimneys.

DIN/EN 1991-1-4 – Actions on structures – Wind actions.

Zone	Description	Basic wind speed v_{b0}	Terrain category	Bearing capacity (A_w)
1	Most part of Nordrhein-Westfalen, Hessen, Rhenland-Pfalz, Saarland, Baden-Wurttemberg, Bayern and Thüringen.	22,5 m/s	II	21 m ²
2	Hamburg, Berlin, Brandenburg, Sachsen-Anhalt, Sachsen and some parts of Schleswig-Holstein Thüringen, Niedersachsen, Mecklenburg-Vorpommern, Bayern and Baden-Wurttemberg.	25 m/s	II	15 m ²
3	Northern part of Schleswig-Holstein, Bremen and Mecklenburg-Vorpommern.	27,5 m/s	II	10 m ²
4	Costal part of Schleswig- Holstein and Bremen.	30 m/s	I	-

A_w is the maximum total wind drag area incl. shape factor, that can be equally distributed over the top 9 m.

Ladder with hoops from base to top – 0,14 m²/m.

The following feeder load is assumed:

0,20 m²/m for each operator, (total of 0,60 m²/m) distributed on 2 sides.

Foundation types:

Normally a traditional Pier & Pad foundation is designed and casted for a TEL tower. Carl C. can assist with the design if required, based on site specific geotechnical specifications.

